



# REFRESHER<sup>®</sup> OASIS<sup>™</sup>

## DRIVE REVENUE WITH SUPERIOR TECHNOLOGY.

The Refresher Oasis was built for long days and busy events with its industry-leading can capacity and enough merchandising space for all your most popular items. With an ELiTE lithium powertrain activated by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gas engine, the Refresher Oasis pushes unparalleled customer service.

**ELiTE**  
LITHIUM

[CUSHMAN.COM](http://CUSHMAN.COM)

**500 CAN**  
CAPACITY

**12.1 SQ FT**  
COUNTER SPACE

**6.7 CU FT**  
MERCHANDISE CABINET

 **CUSHMAN**



# REFRESHER® OASIS™

ELITE LITHIUM

EFI GAS

## BODY & CHASSIS

|                |  |
|----------------|--|
| FRAME          | Welded Steel with E-Coat & DuraShield™ Powder Coat |
| BODY & FINISH  | Injection Molded TPO, Painted (Front)              |
| STANDARD COLOR | Forest Green                                       |

## DIMENSIONS

|                                    |  |
|------------------------------------|--|
| OVERALL LENGTH                     | 117.0 in (297.18 cm)   |
| OVERALL WIDTH                      | 50.8 in (129.032 cm)   |
| OVERALL HEIGHT (NO CANOPY)         | 47.4 (120.40 cm)   |
| OVERALL HEIGHT (WITH CANOPY)       | 73.3 in (186.18 cm)  |
| WHEEL BASE                         | 76 in (193.04 cm)  |
| FRONT WHEEL TRACK                  | 35 in (88.90 cm)   |
| REAR WHEEL TRACK                   | 38.5 in (97.79 cm)   |
| GROUND CLEARANCE                   | 4.5 in (11.43 cm)  |
| REFRESHER UNIT MATERIAL AND FINISH | 5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating |

## POWER

|                    |                                 |  |
|--------------------|---------------------------------|--|
| POWER SOURCE       | 56.7 V Li-Ion Battery           | 4 Cycle 24.5 cu in (401 cc)              |
| MOTOR TYPE         | AC Induction                    | N/A                                      |
| VALVE TRAIN        | N/A                             | Single Cylinder OHV                      |
| HORSEPOWER (KW)    | 14.9 hp (11.1 kW)               | 13.5 hp (10.1 kW)                        |
| ELECTRICAL SYSTEM  | 48V Primary, 12V Auxiliary      | Starter/Generator, Solid-State Regulator |
| BATTERY (QTY/TYPE) | 4.2 ELiTE - Twin Pack           | One 12 Volt Maintenance Free             |
| BATTERY CHARGER    | 811 Watt World Charger          | N/A                                      |
| KEY OR PEDAL START | Pedal                           | Pedal                                    |
| AIR CLEANER        | N/A                             | Industrial Rated Dry Filter              |
| LUBRICATION        | N/A                             | Pressurized Oil System                   |
| OIL FILTER         | N/A                             | Spin-On                                  |
| COOLING SYSTEM     | N/A                             | Air Cooled                               |
| FUEL CAPACITY      | N/A                             | 6.65 Gallon (25 L) tank                  |
| DRIVE TRAIN        | Motor Shaft Direct Drive        | Continuously Variable Transmission (CVT) |
| TRANSAXLE          | Differential with Helical Gears |  |
| GEAR SELECTION     | Forward-Neutral-Reverse         | Forward-Reverse                          |
| REAR AXLE RATIO    | 16.99:1                         | 16.53:1 (Forward) 16.81:1 (Reverse)      |

## PERFORMANCE

|                            |                                       |                      |
|----------------------------|---------------------------------------|----------------------|
| SEATING CAPACITY           | 2-Person                              |                      |
| DRY WEIGHT (W/O BATTERIES) | 1017 lb (461 kg)                      | 1135 lb (514.83 kg)  |
| CURB WEIGHT                | 1098 lb (498 kg)                      | 1175 lb (532.971 kg) |
| VEHICLE LOAD CAPACITY      | 1134 lb (514 kg)                      | 1066 lb (483 kg)     |
| OUTSIDE CLEARANCE CIRCLE   | 21.5 ft (6.5 m)                       |                      |
| SPEED                      | 11 mph ± 0.5 mph (17.7 kph ± 0.8 kph) |                      |

## STEERING & SUSPENSION

|                       |   |
|-----------------------|---|
| STEERING              | Self-Compensating Rack and Pinion           |
| FRONT/REAR SUSPENSION | Leaf Springs with Hydraulic Shock Absorbers |
| SERVICE BRAKE         | Rear Wheel Mechanical Self-Adjusting Drum   |
| PARKING BRAKE         | Self-Compensating, Single Point Engagement  |
| TIRES                 | 18 x 8.5-8                                  |

## ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

## OPTIONS & ACCESSORIES

- Trash/Recycle Bins
- Aluminum Canopy Frame
- Color Options Available for Canopy, Unit & Vehicle
- 3.0 Liter Airpots (2)
- Reversible Airpot Holder
- Humidor
- Consumable Ice Bin
- NSF Rated Ice Sink
- Unique Drainage
- Wheel Covers
- Turf Tires
- USB Outlet
- Glove Box Door and Shelf
- LED Headlights
- LED Taillights/Brake Lights
- Rapid On-Board Charger (ELiTE Only)

**CUSHMAN.COM**